

Receiving Report

Date:

14-12-19

Batch No:

131145

Supplier:

Air dynamic

Dart P/O:

26751

Packing Slip: Yes ☒ No ☐
 Invoice: Yes ☒ No ☐
 Receipt: Cash ☐ Cr ☒
 New Supplier Yes ☐ No ☒

Release Note Attached: Yes ☒ No ☐ N/A ☐
 Waybill Attached: Yes ☒ No ☐
 Shipment Complete: Yes ☒ No ☐ N/A ☐
 QC18 Inspection ☐ N/A ☒
 Work Order ☐ N/A ☒

Discrepancies

Part Number	Description	Quantity Ordered	Quantity Rec'd	Quantity Short	Quantity Inspected	Quantity Rejected	Comment / NCR Number

Initials of Receiver

QC12

SP

Production/Admin:

Date

Received/Costing

Initial

Location



Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
Tel: 613 632 9577
Fax: 613 632 1053

PURCHASE ORDER

Purchase Order ID PO26751

Purchase Order Date 12/8/2014

PO Print Date 12/8/2014

Page Number 1 of 2

Order From : VC-AD001

AIR DYNAMICS
19420B CLARK GRAHAM AVENUE
BAIE D'URFE, QUEBEC H9X 3R8

Ship To : DART AEROSPACE LTD
1270 ABERDEEN
HAWKESBURY, ON K6A 1K7
CANADA

PAID

Contact Name

Vendor Phone

514-457-4287

Ship To Contact

Ship To Phone

Ship Via:

Ship Acct:

Purolator ground collect

Buyer

Customer POID

Customer Tax #

Terms

Currency

FOB

Chantal Lavoie

10127-2607

Net 30

CAD

EXW - (Ex Works)

Line Nbr	Reference Vendor Part Number Line Comments Delivery Comments	Description/ Mfg ID	Req Date/ Taxable Promise Date	CD	Req Qty/ Unit of Measure	PO Unit Price	Extend Pri
1	600.1013	021200-3M TAPE PRIMER 94 PRIMER 24216	12/23/2014 Yes 12/23/2014	FN	1,000.00 Each	\$0.89	\$890.0
Line Total:							\$890.0
2	71401-45	procurement quality clauses	12/23/2014 No 12/23/2014		1.00	\$0.00	\$0.0
Line Total:							\$0.0

PO Instructions: Purolator Acc#7684382

Note:

RELEASE CERTIFICATE

AIR DYNAMICS

19420B Clark Graham Avenue
Baie d'Urfé, Québec, H9X 3R8

AD-1(A)
QTY: 1,000

514-457-4287

NOMENCLATURE TAPE PRIMER (0.66 ML) AMPULE

PART NUMBER 94 (PEN)

MODEL & TYPE

MAKE 3M

SERIAL NUMBER EXP: JUNE 15, 2016

NEW ☒ REPAIRED ☐ INSPECTED ☐ OVERHAULED ☐ MODIFIED ☐

PREVIOUS CERTIFICATION B#30907 LOT#25707141/10354

I HEREBY CERTIFY THAT THE AIRCRAFT PARTS, APPLIANCES AND/OR MATERIALS DESCRIBED HEREON WERE ACQUIRED FROM A SOURCE OF SUPPLY THAT IS CONSISTANT WITH THE CONDITIONS UNDER WHICH THE DEPARTMENT OF TRANSPORT DISTRIBUTOR APPROVAL NO. 12-89 HAS BEEN GRANTED.

DATE DECEMBER 18, 2014

Brenda Sheu
INSPECTOR'S SIGNATURE



JE CERTIFIE PAR LES PRESENTES QUE LES PIECES D'AERONEFS
DECRIRES DANS LE PRESENT CERTIFICAT ONT ETE OBTENUES D'UNE
SOURCE D'APPROVISIONNEMENT CONFORME AUX CONDITIONS
AUXQUELLES LE CERTIFICAT D'AUTORISATION DE DISTRIBUTION
NO. 12-89 DU MINISTERE DES TRANSPORTS A ETE ATTRIBUE.

DATE

18 decembre 2014

SIGNE

Grenda Shea

AD
5

30907



17 DEC. 2014

Certificate of Lot Conformance

3M MILTON DC
2751 PEDDIE RD
MILTON, ON L9T 0K1

AIR DYNAMICS CO LTD
19420 B CLARK GRAHAM AVENUE BAIE D'URFEE
QC, H9X 3R8

Date certificate is prepared: Dec-15-2014

The 3M product listed below was produced in accordance with standard manufacturing processes for the product in effect at the time of manufacture.

3M Invoice Number 4000526520		Customer PO Number 30907	Customer Part Number 10
3M Stock Number 70-0160-5484-6 UPC Number 00021200242168	Product Description 94 PRIMER AMPULE BULK		
Shelf Life 18 MONTHS FROM SHIPMENT DATE		Storage Condition for this Product HUMIDITY CONTROLLED STORAGE (16C/60F TO 27C/80F & 40-60% RH)	
MATERIAL 7000050137			

Lot Number: 25707141/10354


Date of Manufacture: Mar-12-2007

Please contact your 3M Customer Service Representative if you have any questions.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable 3M specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is shown to be nonconforming within the warranty period, your exclusive remedy and 3M's sole obligation will be, at 3M's option, to replace the nonconforming 3M product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

This certificate or any information contained in it does not amend or change any applicable 3M terms and conditions of sale.

Authorized by: Werner Brooks 	Title: C of C picker	Date Signed: Dec-15-2014
---	--------------------------------	------------------------------------

3M Canada Company
 1840 Oxford Street East, Post Office Box 5757
 London, Ontario N6A 4T1
 Medical Emergency Telephone: (519) 451-2500, Ext. 2222
 Transportation Emergency Telephone (CANUTEC): (613) 996-6666

Material Safety Data Sheet

Document id : 07-0925-3 Issue date : 2013/05/21
 Version : 13.00 Supersedes date : 2008/10/13

Copyright, 1997, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Prepared by: Corporate Regulatory Services, 3M Canada Company
 Telephone: (800) 364-3577, Fax: (800) 603-7758, Web Site: www.3M.ca

1 Chemical Product and Company Identification

Tradename:

3M(TM) PRIMER 94 (AMPOULES)

Product ID:

70-0062-1013-5 70-0160-5482-0 70-0160-5483-8 70-0160-5484-6
 70-0160-5498-6 70-0160-5509-0 70-0160-9260-6 70-0160-9261-4
 70-0064-4727-3

Intended Use of Product:

Adhesive primer. Industrial use;

Division:

INDUSTRIAL ADHESIVES AND TAPES

2 Hazards Identification

Critical Hazards:

Extremely flammable liquid and vapour.

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Moderate Skin Irritation: Signs/symptoms can include localized redness, swelling, itching, and dryness.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May be absorbed through skin and cause target organ effects.

May be absorbed following inhalation and cause target organ effects.

May be absorbed following ingestion and cause target organ effects.

METHYL ALCOHOL (67-56-1): can cause birth defects or other

reproductive harm.

High exposures to xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus. These effects were often at levels toxic to the mother. The significance of these findings to humans has not been determined.

TOLUENE (108-88-3): can cause birth defects or other reproductive harm.

WARNING: Contains a chemical which can cause cancer. (CAS 100-41-4) (IARC possible human carcinogen 2B)

See Sections 7 and 11 for further information.

3 Composition/Information on Ingredients

Ingredient Name	CAS Number	Percentage
CYCLOHEXANE	110-82-7	30 - 60
XYLENE	1330-20-7	20 - 35
ETHYL ALCOHOL	64-17-5	5 - 10
ETHYLBENZENE	100-41-4	5 - 10
ACRYLIC POLYMER	Trade Secret	1 - 5
ETHYL ACETATE	141-78-6	1 - 5
CHLORINATED POLYETHYLENE	68609-36-9	0.5 - 1.5
EPOXY RESIN	25068-38-6	0.1 - 1.0
METHYL ALCOHOL	67-56-1	0.1 - 1.0
TOLUENE	108-88-3	0.1 - 0.5

NOTE:

ACRYLIC POLYMER is a Trade Secret material which is not controlled according to WHMIS criteria.

Each percentage is expressed as the ratio of the weight of the ingredient to the weight of the controlled product.

4 First Aid Measures

Instructions for Eye Contact:

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Instructions for Skin Contact:

Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water for at least 20 minutes or until chemical is removed. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Instructions for Inhalation:

If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

Instructions for Ingestion:

Do not induce vomiting unless instructed to do so by medical

personnel. Get medical attention.

5 Fire Fighting Measures

Flash point:

-20.0 C CC

Lower Explosive Limit (%): 1 %
 Upper Explosive Limit (%): 11.2 %
 Autoignition temperature: Not Available
 Suitable Extinguishing Media:

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

Exposure Hazards during Fire:

Closed containers exposed to heat from fire may build pressure and explode. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

Combustion Products from Fire:

Carbon monoxide - During Combustion;

Carbon dioxide - During Combustion;

Unusual Fire and Explosion Hazards

None known.

Fire Fighting Procedures:

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

NFPA: Health 2

NFPA: Fire 3

NFPA: Reactivity 0

NFPA: Unusual Reaction Hazard

none

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

6 Accidental Release Measures

Personal Precautions:

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

3M(TM) PRIMER 94 (AMPOULES)

Page 4 of 11 □

Environmental Procedures

Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Methods for cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Seal the container.

Spill Response:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill.

7 Handling and Storage**Storage Requirements:**

No data available.

Incompatible Materials:

Store away from heat;
Store out of direct sunlight.
Sparks and/or Flames;
Strong oxidizing agents;

Ventilation:

Keep container in well-ventilated area.

Fire Prevention:

Extremely flammable liquid and vapour. No smoking while handling this material.

Explosion Prevention:

Keep away from heat, sparks, open flame, pilot lights and other sources of ignition.

Static Prevention:

Avoid static discharge.

Use Instructions:

Keep container tightly closed. Vapours may ignite explosively. May cause flash fire. Prevent build-up of vapours - open all windows and doors. Maintain vapour concentrations below recommended exposure limits. Use only with cross-ventilation. Without adequate ventilation, vapours may settle in low-lying areas. Keep away from heat, sparks, and open flame. Do not smoke or ignite matches, lighters, etc. Avoid contact with oxidizing agents.

3M(TM) PRIMER 94 (AMPOULES)

Page 5 of 11 □

8 Exposure Controls/Personal Protection**Personal Protection****Eye Protection:**

The following should be worn alone or in combination, as appropriate, to prevent eye contact:

Safety glasses with side shields

Hand Protection:

Wear appropriate gloves when handling this material.

Gloves not normally required.

Skin Protection:

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Respiratory Protection:

Under normal use conditions, airborne exposures are not expected to

be significant enough to require respiratory protection.

Avoid breathing of vapours, mists or spray.

- Select one of the following approved respirators based on airborne concentration of contaminants and in accordance with regulations:
- Half facepiece or fullface air-purifying respirator with organic vapour cartridges.

Ingestion (Prevention):

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

Keep out of the reach of children.

Recommended Ventilation:

Use with appropriate local exhaust ventilation.

Use in an enclosed process area is recommended.

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment.

Ingredient Exposure Data

CYCLOHEXANE (110-82-7)

LD50 (rat, oral) 12,705 mg/kg

LC50 (rat, inhalation/4 hours) 13.9 mg/l

Exposure Limits

ACGIH: TWA 100 ppm 100 ppm ACGIH: TWA

XYLENE (1330-20-7)

LD50 (rat, oral) 3523 mg/kg

LD50 (dermal, rabbit) > 1700 mg/kg

3M(TM) PRIMER 94 (AMPOULES)

Page 6 of 11 □

LC50 (rat, inhalation/4 hours) 5000 ppm

Exposure Limits

ACGIH: TWA 100 ppm (Table A4)

ACGIH: TWA 434 mg/m3 (Table A4)

ACGIH: STEL 150 ppm (Table A4)

ACGIH: STEL 651 mg/m3 (Table A4)

CMRG: TWA 50 ppm

CMRG: STEL 75 ppm

150 ppm ACGIH: STEL 100 ppm ACGIH: TWA 75 ppm CMRG: STEL 50 ppm CMRG: TWA

ETHYL ALCOHOL (64-17-5)

LD50 (rat, oral) 7060 mg/kg

LC50 (rat, inhalation/4 hours) No data available.

Exposure Limits

ACGIH: STEL 1000 ppm (Table A3)

1000 ppm ACGIH: STEL

ETHYLBENZENE (100-41-4)

LD50 (rat, oral) 3500 mg/kg

LD50 (dermal, rabbit) 17800 uL/kg

LC50 (rat, inhalation/4 hours) No data available.

Exposure Limits

ACGIH: TWA 20 ppm (Table A3)

CMRG: TWA 25 ppm

CMRG: STEL 75 ppm

20 ppm ACGIH: TWA 75 ppm CMRG: STEL 25 ppm CMRG: TWA

ACRYLIC POLYMER (Trade Secret)

Specific Ingredient Data

No data available.

LD50 (rat, oral)	No data available.
LC50 (rat, inhalation/4 hours)	No data available.
Exposure Limits	
No data available.	
ETHYL ACETATE (141-78-6)	
LD50 (rat, oral)	5600 mg/kg
LD50 (dermal, rabbit)	> 20 ml/kg
LC50 (rat, inhalation/4 hours)	40.7 mg/l (11,300 ppm)
Exposure Limits	
ACGIH: TWA 400 ppm	
ACGIH: TWA 1440 mg/m3 400 ppm ACGIH: TWA	
CHLORINATED POLYETHYLENE (68609-36-9)	
Specific Ingredient Data	
No data available.	
LD50 (rat, oral)	> 5000 mg/kg
LC50 (rat, inhalation/4 hours)	No data available.
Exposure Limits	
No data available.	
EPOXY RESIN (25068-38-6)	
LD50 (rat, oral)	11400 mg/kg
LD50 (dermal, rabbit)	23.4 g/kg
LC50 (rat, inhalation/4 hours)	> 791 mg/m3

3M(TM) PRIMER 94 (AMPOULES)

Page 7 of 11 □

Exposure Limits	
No data available.	
METHYL ALCOHOL (67-56-1)	
LD50 (rat, oral)	5600 mg/kg
LD50 (dermal, rabbit)	15800 mg/kg
LC50 (rat, inhalation/4 hours)	64000 ppm
Exposure Limits	
ACGIH-TWA: 200 ppm (skin contact contributes to exposure)	
ACGIH: STEL 250 ppm (skin contact contributes to exposure) 250	
ppm ACGIH: STEL; skin contact contributes to exposure 200 ppm	
ACGIH: TWA; skin contact contributes to exposure	
TOLUENE (108-88-3)	
LD50 (rat, oral)	636 mg/kg
LD50 (dermal, rabbit)	14100 uL/kg
LC50 (rat, inhalation/4 hours)	LC50 (female rat, inhalation/4 hours vapour): 19.0 mg/l
Exposure Limits	
ACGIH: TWA 20 ppm (Table A4)	
CMRG: STEL 75 ppm (Skin contact contributes to exposure)	

9 Physical and Chemical Properties

Physical form, Color, Odour:	Liquid; amber; solvent odour;
Odour Threshold:	No data available.
pH:	Not applicable
Boiling point/boiling range:	76.7 C
Melting point/melting range:	Not applicable
Vapour pressure:	68 mmHg at 20 C
Water Solubility:	Negligible
Partition coefficient (K o/w):	Not Available
Specific gravity:	0.82 Water=1 at 25 C

Vapour density:	Not Available
Volatile organic compounds:	781 gms/liter SCAQ443 (low solids less exempts)
Evaporation rate:	Not Available
Viscosity:	1 - 35 centipoise at 23 C
Percent Volatile:	95.3 - 97 % by weight
	Estimated

3M(TM) PRIMER 94 (AMPOULES)

Page 8 of 11 □

10 Stability and Reactivity

Conditions to Avoid:

Sparks and/or Flames;

Heat;

Store out of direct sunlight.

Materials to Avoid:

Strong oxidizing agents;

Hazardous Decomposition:

Carbon monoxide - During Combustion;

Carbon dioxide - During Combustion;

Stability and Reactivity:

Stable. Hazardous polymerization will not occur.

11 Toxicological Information

Effects from Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Effects from Skin Contact:

Moderate Skin Irritation: Signs/symptoms can include localized redness, swelling, itching, and dryness.

Prolonged or repeated exposure may cause: Dermal Effects:

Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May be absorbed through skin and cause target organ effects.

Effects from Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Effects from Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Chemical (Aspiration) Pneumonitis: Signs/symptoms can include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and possibly death.

May be absorbed following ingestion and cause target organ effects.

Sensitization Information:

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Carcinogenicity:

WARNING: Contains a chemical which can cause cancer. (CAS 100-41-4) (IARC possible human carcinogen 2B)

Note: This product contains ethanol. In IARC published Monograph

3M(TM) PRIMER 94 (AMPOULES)

Page 9 of 11 □

No. 44, entitled, 'Alcohol Drinking', the carcinogenicity of ethanol was determined based on chronic exposure to ethanol through human consumption of alcoholic beverages. This is not an expected effect during the foreseeable use of this product.

Mutagenicity:

No data available.

Reproductive Effects:

METHYL ALCOHOL (67-56-1): can cause birth defects or other reproductive harm.

High exposures to xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus. These effects were often at levels toxic to the mother. The significance of these findings to humans has not been determined.

TOLUENE (108-88-3): can cause birth defects or other reproductive harm.

Component Based Information:

No data available.

Product Based Information:

No data available.

Other Effects & Information:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

12 Ecological Information

Environmental Data:

Ecotoxicity Data:

Not determined.

Ecofate Data:

Not determined.

Special statements for 2001/58/EC:

One or more components of this product have significant known or predicted environmental hazards, but a conservative assessment indicates a low environmental risk. Intended use and proper disposal are unlikely to cause the environmentally hazardous component(s) to enter the environment in quantities or by routes that could cause the adverse environmental impacts. Handling this product according to recommendations is important to minimize release to the environment. It is recommended that the environmental information included in this section be used to help determine appropriate handling of this product for your uses.

3M(TM) PRIMER 94 (AMPOULES)

Page 10 of 11 □

Other Effects and Information:

- Product usages, or other lifecycle stages, are expected to release volatile organic compounds (VOCs) to the atmosphere. Regulations may restrict the release of VOCs because they contribute to the formation of ozone and smog. Regulatory definitions for VOC vary. Because of smog and other impacts, releases through evaporation or other means should be minimized to the extent possible.

13 Disposal Considerations

Product as Sold:

No data available.

Product Packaging:

No data available.

Special Instructions:

Since regulations vary, consult applicable regulations or authorities before disposal.

14 Transport Information

Transportation of Dangerous Goods

TDG Classification:

Consumer Commodity

Special Information:: Contact 3M for more information.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for Canadian ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

3M(TM) PRIMER 94 (AMPOULES)

Page 11 of 11 □

15 Regulatory Information

WHMIS Classification:

B2, D2A, D2B

NOTE:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Product Certifications:

The product on this MSDS, or all its components, is included on the following countries' chemical inventories, as noted:

EINECS - European Inventory of Existing Commercial Chemical Substances

TSCA - Toxic Substances Control Act (USA)

- * The components of this product are in compliance with the chemical notification requirements of CEPA.

16 Other Information

Reason for Reissue:

The following Sections and topics have been updated or revised:

Section 2 - Hazards Identification - Critical Hazards;

Section 4 - First Aid Measures;

Section 6 - Accidental Release Measures;

Section 7 - Handling and Storage;

Section 8 - Exposure Controls/Personal Protection;

Section 9 - Physical and Chemical Properties;

Section 11 - Toxicological Information;

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

---End---